## essentials™

Product Code: CL051

## **Technical Specification**





## **General Information**

Dimensions 80mm (W) x 80mm (H) x 42mm (D)

Finish Metal Clad Grey

Materials Front Plate & Pattress Box: Electrophoretically Coated Steel

Insert, Switch, Fuse Drawer & Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

**Terminal Capacity** 4 x 2.5mm<sup>2</sup> or 2 x 4mm<sup>2</sup>

Switched Yes
Double Pole Yes
Twin Earth Terminals Yes

Fuse Fitted 13A (BS 1362)

Flex Outlet Yes (10mmø Through Front of the Plate)

Back Box Depth 40mm Supplied

Earth Terminal Provided Yes

Back Box Knockouts 5 x 20mm (2 on top, 1 on bottom, 1 on each side)

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS 1363-4: 2016 +A1: 2018

BS 1362:1973

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



